



CDM6010 MINI EXCAVATOR

TECHNICAL PARAMETERS

Name		Data
Basic	Operating weight	1010 kg
	Standard bucket Capacity	0.022 m ³
	Standard bucket Width	320 mm
	Max.Travel speed	1.5/2.9 km/h
	Max.Swing speed	8.2 rpm
	Grade ability	30°
	Ground pressure	24.5 kPa
	Boom swing angle (L/R)	73°/53°
Engine	Max.Traction force	10 KN
	Engine brand	Yanmar
	Engine model	2TNV70-PSU
	Rated power	7.2 kW/2400 rpm
	Displacement	0.57 L
Hydraulic	Fuel tank	9.4 L
	Max.Flow(total)	9.6×3 L/min
	Max.Working pressure	16 MPa
	Max.Pilot pressure	3.2 Mpa
	Max.Arm digging force	5.8 kN
	Max.Bucket digging force	9.4 kN
	Hdraulic oil tank	9.5 L
Chassis	Track width	180 mm
	Track type	Rubber crawler
	Carrier rollers number	1(each side)
	Track rollers number	2(each side)
Electric	System vottage	12 V
	Battery capacity	12 V,36 Ah

PRODUCT FEATURES

- Yanmar Strong Power Engine.Emission level reaches EU Stage V . Trustworthy on compact equipment, this engine features low noise, low vibration, and easy maintenances for main parts.
- Telescopic chassis controlled by simple single joystick, the chassis width can be retracted to 750mm to adapt to narrow spaces. Onthe contrary, the chassis width can be extended to 1000mm to improve the stability by 15% and even allow the use of hydraulic breaking hammer.
- The hydraulic pilot control is firstly applied for the working device,featuring better accuracy and smoothness
- 3 hoisting points are provided fot direct hoisting and ensure easy loading and unloading, featuring high safety and simplicity.
- The tiltable engine hood allows the exposure of most engine area to ease the repairs.

STANDARD EQUIPMENT

- Tops canopy
- Safety seat belt
- Telescopic chassis
- Hydraulic pilot control rod
- Deflectable boom
- Warning light
- External centralized pressing gauge

OPTIONAL

- Quick change device
- Narrow bucket
- Widened bucket
- Attachment pipelines



The following blank can be used for notes or comments

For more information on Lonking products,Please contact our local agent:

Lonking, Lonking CD Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd. and may not be used without written permission. 2023/07

Specifications and design are subject to change without prior notice. Machines shown may not include optional accessories.

LONKING (FU JIAN) INTERNATIONAL TRADE CO.,LTD.
 Add: 26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai
 E-mail: export@lonking.cn http://www.lonkinggroup.com
 Tel: +86-21-3760 2242

- OPERATING WEIGHT: 1010kg
- ENGINE POWER: 7.2kW
- BUCKET CAPACITY: 0.022m³
- TRAVEL SPEED: 1.5/2.9km/h