


TECHNICAL PARAMETERS

ITEM		UNIT	CDM6306	
Basic	Operating weight	kg	32800	
	Boom length	mm	6150	
	Arm length	mm	3200	
	Standard bucket	m³	1.6 (Rock)	
	Max.Travel speed	km/h	3.4-5.2	
	Max.Swing speed	rpm	9.5	
	Grade ability	0	35(70%)	
	Ground pressure	kPa	62	⊢∣
	Max.Traction force	kN	283	F
Engine	Engine model		QSL9	
	Rated power	kW/rpm	209/2100	Ľ
	Max.Torque	Nm/rpm	1472/1400	
	Displacement	L	8.9	
	Fuel tank	L	600	
Hydraulic	Max.Flow(total)	L/min	288×2	
	Max.Working pressure	MPa	34.3	
	Max.Pilot pressure	MPa	3.9	
	Max.Arm digging force	kN	170	C
	Max.Bucket digging force	kN	220	
	Hydraulic oil tank	L	300	В
Chassis	Track width	mm	600	v
	Track shoes number		47×2	v
	Carrier rollers number		2×2	Т
	Track rollers number		8×2	F
Electric	System vollage	V	24	7
	Battery capacity	V/Ah	24/165×2	8





PRODUCT FEATURES

Cummins strong power engine. Emission standard meets EPA tier 4F and EU stage V.
Dptimized Cooling System to Reduce Power Loss and Noise
Advanced Control System
Combined C type closed frame improves rigidity and strength of rotary platform.
Comfortable ROPS Cabin with 2.7m ³ Operational Space
No Frame Cab Glasses to Enlarge Operation Field of View
Rock Track Shoes, Chassis Reinforcement, More reliable and Near-resistant
Heavty-duty Working Device with High Strength Low Alloyed Steels

OPTIONAL

Breaking hammer & pipeline				
Work warning light				
Walking alarm				
Top protecting net				
Front protecting net				
700mm triple grouser shoes				
800mm triple grouser shoes				



The following blank can be used for notes or comments

For more information on Lonking products, Please contact our local agent;

LONKING (FUJIAN) INTERNATIONAL TRADE CO., LTD.

Add: 26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai E-mail: export@lonking.cn http://www.lonkinggroup.com Tel: +86-21-3760 2242

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd. and may not be used without written permission. 2024/05

Specifications and design are subject to change without prior notice. Machines shown may not include optional accessories.

CDM6306 HYDRAULIC EXCAVATOR

OPERATING WEIGHT:	32800kg
ENGINE POWER:	209kW
BUCKET CAPACITY:	1.6m ³
TRAVEL SPEED:	3.4/5.2km/h